

Endless 6282 Opal Prismatic Linear Light



Product Code	LUL6282-O-P
TYPE	Surface, Suspended or recessed
Profile Options	Direct, Direct/ Indirect
Diffuser Options	Opal (Standard), Prismatic
Size	62mm x 82mm
Dimension	575mm, 855mm, 1135mm, 1415mm, 1695mm, 1975mm, 2255mm
Direct Illumination	15W, 22W, 30W, 38W, 45W, 52W, 60W
Indirect Illumination	7W, 11W, 15W, 19W, 22W, 26W, 30W
Lumens	Up to 101lm/W
Power Factor	>0.90
Dimmable Option	Non-Dimmable, 1-10V Dimming, TRIDONIC DALI Dimmable
Voltage	240V
Beam Angle	Prismatic 85°. Opal (Standard) 120°
Colour Deviation	SDCM≤3
UGR (Unified Glare Rating)	<22 (Opal), <19 (Prismatic/ Baffle)
IP	20 or 40
Colour Temperature	2700K, 3000K, 4000K
LED Chips	SAMSUNG CRI82
Average Rated Life	50,000 hours
Material	Aluminum alloy 6063
Color	Textured Black, Textured White or Custom colour
Warranty	7 Years
Certifications	SAA, C-tick, CE, RoHS