



#### Installation Instructions:

Turn off the power

- <A>. Cut out the hole on the false ceiling, and put the main wire(3) out of the hole. Install the hanging plate(5) to the false ceiling with the self-tapping screws(5), adjust the height of the wire(3), then fix the wire(3) to the wire locker(4) with the screws(5). Install the aluminum part(6) to the hanging plate(1).
- <B>. Install the hanging plate(7) to the false ceiling with the screws(8), contact the output wire of the driver to the lamp with the terminal(10), then contact the input wire of the driver to the main wire with the terminal(9). Install the canopy(12) to the hanging plate(7) with the screws(11).
- <C>. Install the glass(14) into the tube(13), and fix it with hex screws(15), then install the other glasses in the same way.
- <D>. Turn on and test the power

Voltage: 100-240V    50\60HZ    Bulb: LED    6\*3W    3000K

#### NOTES:

- 1. Please wear cotton gloves during installment to avoid scratches on the surface of lamp.
- 2. Glass is fragile, please take care during the installation.
- 3. Please consult a qualified electrician if there are any abnormalities.

When installing any electrical item, please make sure all mains electricity supply is isolated, then continue the installation under our instructions.  
We will not take any responsibilities for any breakages caused by incorrect installation.

PLEASE KEEP THIS INSTRUCTION MANUAL AFTER INSTALLATION