

Magnetic Track Adjustable Spotlight



Magnetic Track Adjustable Spotlight delivers flexible, precise illumination with adjustable aiming and multiple wattage options, ideal for task, display and accent lighting in modern residential and retail spaces.

Are you a professional and your project needs some support?

BOOK A CONSULTATION WITH US

Main Specifications

Type: Magnetic Track Spotlight	Lumen Output: 4W 3000K CRI92 320lm; 7W 3000K CRI92 560lm; 12W 3000K CRI92 960lm; 15W 3000K CRI92 1200lm; 20W 3000K CRI92 1600lm
Light Source: 4W / 7W / 12W / 15W / 20W dedicated phosphor LED (non-replaceable)	SDCM / Lifetime: ≤3 SDCM / L70 B10 50,000 hours
Colour Temperature / CRI: 3000K / 3500K / 4000K, CRI ≥92	Dimensions: 4W Ø35 × L55mm; 7W Ø45 × L70mm; 12W Ø55 × L86mm; 15W Ø55 × L118mm; 20W Ø55 × L150mm
Beam Angle: 15° / 24° / 38°	Power Supply: DC 48V
Optic: Precision polycarbonate optic	IP Rating: IP20
Body: Die-cast aluminium adjustable housing with powder-coated finish	Weight: Approx. 0.5kg
Dimming Options: Non-dimmable standard; DALI dimmable available (+AUD \$50 per light)	Adjustability: Fully adjustable spotlight head
Finish: Black or White	

