



NOVA 75 Square Architectural Downlight

The NOVA 75 Square is a refined architectural downlight by Lucretia, combining a minimalist square design, advanced glare control, precision optics and modular serviceability to deliver comfortable, reliable lighting for contemporary architectural spaces.

Are you a professional and your project needs some support?

BOOK A CONSULTATION WITH US

Main Specifications

Type: Square Architectural Recessed LED Downlight

Installation: Recessed with Trim

Power Options: 12W · 15W

Luminous Flux: Up to 1050 lm

Luminaire Efficacy: Up to 70 lm/W

Colour Temperature: 2700K · 3000K · 3500K · 4000K
Custom CCT available on request

Colour Rendering: CRI 95+

Colour Consistency: SDCM <3

Beam Angles: 15° · 24° · 36° · 50°

Optical System: NOVA Optical Engine with deep recessed optics, precision reflector, anti-glare lens and optional honeycomb louvre

Glare Control: NOVA Visual Comfort System featuring advanced four-layer anti-glare technology

Light Source: High-performance LED module

Construction: Precision die-cast aluminium housing with integrated thermal management architecture

Reflector Finishes: White · Silver · Metallic Black · Matte Black
Custom finishes available on request

Control Options: TRIAC (Standard) · DALI · 0–10V · Casambi
Additional control protocols available on request

Input Voltage: 220–240V AC · 50/60Hz

Dimensions: 85 × 85 × H93 mm

Cut-Out: 75 × 75 mm

Material: Die-cast Aluminium

Ingress Protection: IP44

Serviceability: LED module and driver replaceable from below the ceiling without removing the complete luminaire

Customisation: Custom beam angles, colour temperatures, reflector finishes and control solutions available for project requirements

Warranty: 5-Year Warranty

Applications: Luxury Residential · Hospitality · Retail · Gallery · Museum · Commercial

